

### BS-2036F(LED) Fluorescent Biological Microscope

#### Introduction

BS-2036F(LED) Series LED fluorescence microscopes are newly developed microscopes, the microscopes use LED as the light source, the life span of the LED lamp is much longer than mercury lamp, the performance is also better. It has 6 turret positions for filter cubes, more filter cubes can be used without change the blocks.

#### Features

- 1. Excellent fluorescent image with infinite optical system.
- 2. LED illumination with 50,000 hours life span.
- 3. Convenient to use, no need warm-up.
- 4. No need for cooling due to LED cold light source.
- 5. 6 positions for filter cubes.

#### Application

BS-2036F(LED) series LED Fluorescence microscopes are used to study the absorbing, transportation, chemicals distribution and positioning in cells. They are widely used in disease examination, immune diagnosis and life science areas.

#### Specifications

Item	Constituent	BS-2036	BS-2036
	Specification		FT(LED)
Optical System	Infinite Optical System	•	•
Viewing Head	Seidentopf Binocular Viewing Head, Inclined at 30°, 360° Rotatable,		
	Interpupillary 50-75mm	•	
	Seidentopf Trinocular Viewing Head, Inclined at 30°, 360° Rotatable,		•
	Interpupillary 50-75mm		
	Seidentopf Binocular/Trinocular Viewing Head, Inclined at 30°, 360° Rotatable,	0	0

# BestScope

# Beijing BestScope Technology Co., Ltd.

	Interpupillary 48-75mm					
Eyepiece	WF10×/20mm				•	•
	WF16×/13mm				0	0
	Reticule Eyepiece WF10×/20mm (0.1mm)					0
Objective	Infinite E-Plan Achromatic Objective 4×, 10×, 40×, 100×(Oil)				٠	•
	Infinite Plan Achromatic Objective 4×, 10×, 20×, 40× (S), 60× (S), 100× (Oil) (S)				0	0
Nosepiece	Backward Quadruple Nosepiece				•	•
	Backward Quintuple Nosepiece					0
Focusing	Coaxial Coarse & Fine Foc	٠	•			
Stage	Stage Size: 145×140mm, Cross Travel 76×52mm, Two Slide Holder				٠	•
	Rackless Double Layers Mechanical Stage, Size: 182×140mm, Cross Travel					
	77×33mm, Two Slide Hold	0	0			
Condenser	Abbe Condenser NA1.25 with Iris Diaphragm					•
Transmitted Illumination	6V/20W Halogen Lamp, Brightness Adjustable				•	•
	6V/30W Halogen Lamp, Brightness Adjustable				0	0
	3W-LED Illumination Systems (non-rechargeable), Brightness Adjustable				0	0
	0.3W-LED Illumination Systems (Rechargeable), Brightness Adjustable					ο
Optional Accessories	Field Diaphragm, Photo adapters(for DSLR cameras), Video adapters(1X, 0.5X), Polarization set, Phase contrast kit, filters, mirror, Cable Winding Device					0
Reflected Light Source		Excitation	Dichroic Mirror	Barrier Filter		
	Blue excitation	420-490	505	520	•	•
	Green excitation	500-550	575	590	•	•
	Ultraviolet Excitation	330-380	400	435	0	0
	Violet Excitation	380-420	430	460	0	0
Fluorescent Lamp	3W LED Lamp					•
Package	42cm*28cm*45cm, 40cm*20cm*40cm, 12kg					•

Note: •Standard Outfit, OOptional

## Sample Images

