

BS-6003 Inverted Metallurgical Microscope



Introduction

BS-6003 inverted metallurgical microscope is widely used in schools and laboratory to identify and analyze structure of metals and alloys, as well as do researching on metallurgical material after heating.

Feature

- 1. Perfect for education, experiment and normal testing.
- 2. Easy operation, also supply high quality image.

Specification

| Item | Specification | BS-6003M | BS-6003B | BS-6003T |
|----------------|---|----------|----------|----------|
| Optical System | Finite optical system | • | • | • |
| Viewing Head | Monocular viewing head | • | 0 | 0 |
| | Sliding binocular viewing head | 0 | • | 0 |
| | Tinocular viewing head | 0 | 0 | • |
| | Integrated sliding binocular digital head(3.0MP) | 0 | 0 | 0 |
| Eyepiece | Wide field eyepiece WF10×/18mm | • | • | • |
| | Wide field eyepiece WF12.5×/14mm | • | • | • |
| | Wide field eyepiece WF16×/11mm | 0 | 0 | 0 |
| Objective | Achromatic objective 10×/0.25, WD=6.3mm | • | • | • |
| | Plan achromatic objective 40×/0.65, WD=0.7mm | • | • | • |
| | LWD Plan achromatic objective 50×/0.75, WD=2mm | 0 | 0 | 0 |
| | Achromatic objective 100×/1.25(oil), WD=0.1mm | • | • | • |
| Nosepiece | Triple nosepiece | • | • | • |
| Focusing | Coaxial coarse and fine adjustment, Fine division 0.002mm, Focusing | • | • | • |
| | range 30mm | | | |
| Stage | Mechanical stage 180×155mm, Moving range 40×30mm, Stage Clips | • | • | • |
| Illumination | Kohler illumination, 12V/20W Halogen lamp, brightness adjustable | • | • | • |
| Filter | Blue, Green, Yellow and Ground filter | • | • | • |

Note: ● Standard Outfit, ○ Optional